

Injection Performances

Injection capacity for the modulation service or Pimod

Under the assumption that storage space made available to Users in T.Y. 2015/2016 is completely emptied, Edison Stoccaggio defines the Injection capacity for the modulation service (Pimod), expressed in kWh/d, that the User can utilize in every Gas-Day during the contractual period.

During the Injection Period, the Pimod is defined on the basis of the overall injection curve of the hub storage, reprocessed through the definition of the intervals and relevant coefficients, in order to take into account the actual volumes injected in the storage by the User.

In accordance with the art 14.3 of the deliberation 119/05, with the aim to guarantee the adequate flexibility to the User during the Injection Period, Edison Stoccaggio determines the minimum and maximum stock allowed to the User at the end of every month of such period, with reference to the capacity assigned to the User.

Injection Performance ($P_{\text{Imod}} = c \times C_{\text{Imod}}$) valid during the Injection period are set here below, while the value of Pimod during Withdrawal Period is equal to 5.500.000 kWh/g:

$\leq \text{INV} \% <$		c	c1	c2	PI mod
0,00%	76,00%	1	0,25	-	63.500.000
76,00%	100%	0,95	-	0,4167	60.325.000

Coefficient c1 is applied to the period 1st-17th April

Coefficient c2 is applied to the period 1st-14th October